



Low-cost, fully integrated soil moisture loggers with Bluetooth wireless data offload. Available in two models – one that measures soil moisture (HOBOMX2306) and one that measures both soil moisture and temperature (HOBOMX2307) – these loggers are ideal for researchers and growers looking for the accurate data they need to save water, improve crop yields, reduce harmful runoff, and protect ecosystems.

With just a mobile phone, tablet, or Windows laptop running Onset's free HOBOnet app, users get convenient wireless setup and data download via Bluetooth when within 100 feet of the logger – making it easy to retrieve data from hard-to-access field locations. And for indoor areas, such as greenhouses, users can add the MX Gateway for remote access to data in Onset's cloud-based HOBOLink software.

Features:

- Ready to deploy, with pre-attached sensors
- Easy configuration and data offload with the free HOBOnet app
- Durable TEROS 10 soil moisture sensor lasts over 10 years in the field
- For use in both mineral soils and soilless media
- Sturdy, sharp stainless-steel spikes for easy installation and better soil contact
- Option to view data in Percent of Field Capacity

Technical Specifications:**Soil Moisture: Volumetric Water Content (VWC)**

| | | |
|------------------------|---|---|
| Measurement Range* | : | 0.00 to 0.64 m ³ /m ³ in mineral soils 0.00 to 0.70 m ³ /m ³ in soilless media |
| Accuracy | : | ±0.031 m ³ /m ³ typical in mineral soils that have solution EC <8 dS/m ±0.051 m ³ /m ³ typical in soilless media |
| Resolution | : | 0.001 m ³ /m ³ |
| Dielectric Measurement | | |
| Frequency | : | 70 MHz |

Temperature Sensor (MX2307)

| | | |
|---------------|---|--|
| Range | : | -40 to 100°C (-40 to 212°F), with tip and cable immersion in fresh water up to 50°C (122°F) for one year |
| Accuracy | : | ±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F) |
| Resolution | : | 0.04°C (0.072°F) |
| Drift | : | <0.01°C per year (0.018°F per year) |
| Response Time | : | 3 minutes in air moving 1 m/s; 20 seconds in stirred water 4 minutes in air moving 1 m/s with RS3-B Solar Radiation Shield |

Logger

| | | |
|------------------------|---|---|
| Operating Range | : | -25° to 60°C (-13° to 140°F) |
| Radio Power | : | 1 mW (0 dBm) |
| Transmission Range | : | Approximately 30.5 m (100 ft) line-of-sight |
| Wireless Data Standard | : | Bluetooth Low Energy (Bluetooth Smart) |
| Logging Rate | : | 1 second to 18 hours |
| Logging Modes | : | Fixed interval (normal, statistics) or burst |
| Memory Modes | : | Wrap when full or stop when full |
| Start Modes | : | Immediate, push button, date & time, or next interval |
| Stop Modes | : | When memory full, push button, date & time, or after a set logging period |
| Time Accuracy | : | ±1 minute per month 0° to 50°C (32° to 122°F) |
| Battery Type | : | 2/3 AA 3.6 Volt lithium, user replaceable |

| | |
|---------------------------|--|
| Battery Life | : 2 years, typical with logging interval of 1 minute and Bluetooth Always On enabled; 5 years, typical with logging interval of 1 minute and Bluetooth Always On disabled. Faster logging intervals and statistics sampling intervals, burst logging, remaining connected with the app, excessive downloads, and paging may impact battery life. |
| Memory | : 110,000 measurements, maximum (472 kB) |
| Full Memory Download Time | : Approximately 60 seconds; may take longer the further the device is from the logger |
| Dimensions | : Logger housing: 10.8 x 5.08 x 2.24 cm (4.25 x 2.0 x 0.88 in.) Soil moisture sensor: 7.5 x 5.1 x 2.4 cm (2.95 x 2.02 x 0.95 inches) Soil moisture sensor needle length: 5.4 cm (2.13 inches) Soil moisture sensor needle diameter: 0.32 cm (0.13 inches) Temperature sensor (MX2307) diameter: 0.53 cm (0.21 in.) |
| Sensor cable length | : 2 m (6.56 ft) |
| Weight | : MX2306: 229 g (80 oz), MX2307: 267 g (94 oz) |
| Materials | : Logger: Acetal, silicone gasket, stainless steel screws Soil Moisture Sensor: ASA plastic body with polyurethane epoxy filling and stainless steel pins Temperature Sensor (MX2307): Stainless steel waterproof tip Cable: PVC, UV resistant and rodent repellent (soil moisture sensor cable) |
| Environmental Rating | : Temperature sensor and cable (MX2307): Immersion in water up to 50°C (122°F) for 1 year |